



## VOILA LED ACCESS

Wall mounted luminaire type VOILA LED ACCESS from SÉCURLITE or technically equivalent:

- Dimensions: Ø 340 x 105 mm
- Class II - IP55 – IK10 / 20J - VK26 – 850°C - CRI 80 – SDCM 5 – photobiological hazard: RG0
- Polycarbonate base available in white
- Opalescent polycarbonate diffuser with 3 captive vandal-resistant stainless steel screws
- Anti-rip-out-skirt, 4 internal fixing points
- Side cable entries for plastic conduit for renovation – supply terminal block: automatic dual-entry for 1.5 mm<sup>2</sup> conductors
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection, with detection + extinction or standby warning. *Refer to the technical data sheet according to product code*
- Range available in 4000 K
- Lumen maintenance: L70B10 / 56,000 hr – 3-year warranty
- Eligible for the BAR-EQ-110 for the detection versions
- EPD available for ON/OFF version: <https://register.pep-ecopassport.org>
- EPD available for controllable version: <https://register.pep-ecopassport.org>
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

*Technical and dimensional data are given for information only and may be modified at any time without notice.  
Please enquire before ordering*