



EFFICE LED FOR CORRIDORS

Ceiling mounted **only** luminaire type EFFICE CORRIDORS from SÉCURLITE or technically equivalent:

- Dimensions: 350 x 350 x 65 mm
- Class II – IP55 – IK10 / 20J – VK25 – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Polycarbonate base and skirt available in white, grey
- Clear polycarbonate diffuser + optics with 4 captive vandal-resistant stainless steel screws
- Internal polycarbonate reflector
- 2 cable entries for 20,5 mm conductors
- Side cable entries for plastic conduit for renovation – supply terminal block: automatic dual-entry for 1.5 mm² conductors
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection, DALI dimmable, with Pro detection + extinction or standby warning, with Pro detection + radio control, with Pro detection + extinction or standby warning + radio control, slave version + extinction or standby warning, slave version + extinction or standby warning + radio control. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr – 5-year warranty
- Eligible for the BAR-EQ-110 for the detection versions
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

*Technical and dimensional data are given for information only and may be modified at any time without notice.
Please enquire before ordering.*