



Wall or corner or flush-mounting luminaire type TITAN COMPACT LED from SÉCURLITE or technically equivalent:

- Dimensions wall: 375 or 660 or 945 or 1230 mm x 110 x 60 mm
- Dimensions angle: 375 or 660 or 945 or 1230 mm x 95 x 95 mm
- Dimensions flush mounting: 390 or 675 or 960 or 1245 mm x 125 x 75 mm
- Class I – IP65 - IK10++ / 80J –VK45 wall mounted – VK46 ceiling and angle mounted – VK46 flush-mounting stainless steel version – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Wall or corner mounting versions: body and frame in ZP steel, graphite grey colour
- Flush-mounting version: body and frame in painted 304L stainless steel, graphite grey colour or 316L brushed stainless
- Polyester powder-coated finish
- Flat opal polycarbonate diffuser
- Stainless steel vandal-resistant screws
- 2 side cable entries for M20 cable gland (not supplied)
- Supply terminal block: automatic, dual-entry
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr – lumen maintenance: L90B50 / 52,000 hr - 5-year warranty
- Eligible for the RES-EC-104 (wall mounted/E versions: ceiling mounting only, angle version: wall mounted) energy economy certificates
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

*Technical and dimensional data are given for information only and may be modified at any time without notice.  
Please enquire before ordering..*