



Wall or corner-mounted or flush-mounting luminaire type TITAN LED from SÉCURLITE or technically equivalent:

- Dimensions wall TITAN C95: 720 or 1330 mm x 200 x 92 mm
- Dimensions angle 45° TITAN A45: 720 or 1330 mm x 160 x 160 mm
- Dimensions angle 30° TITAN A30: 720 or 1330 mm x 180 x 141 mm
- Dimensions flush-mounting TITAN E: 730 or 1340 mm x 210 x 100 mm
- Class I – IP65 – IK10++ / 120J – VK56 angle and ceiling, VK55 wall – 850°C – CRI 80 – SDCM 3 - photobiological hazard: RG0
- Wall (TITAN C95) or 45° (TITAN A45) or 30° (TITAN A30) corner-mounted versions: body and frame in ZP steel, graphite grey colour
- Flush-mounting version (TITAN E): body and frame in painted 304L stainless steel or all stainless steel in brushed 316L stainless steel
- Polyester powder-coated finish
- Braced opal polycarbonate diffuser
- Stainless steel vandal-resistant screws
- 2 cable entries for M20 cable gland on side panels
- Sliding, plug-in gear-tray
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr – lumen maintenance: L90B50 / 52,000 hr - 5-year warranty
- Eligible for the BAR-EQ-110 for detection versions, BAT-EQ-127 for Dali version with light output ≥ 3000 lm, RES-EC-104 (C95 version: ceiling mounting only, A30 version: wall mounted) energy economy certificates
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

*Technical and dimensional data are given for information only and may be modified at any time without notice.
Please enquire before ordering.*