



Wall or angle or flush-mounting luminaire type TITAN S LED from SÉCURLITE or technically equivalent:

- Wall version dimensions TITAN S3: 410 mm x 225 mm x 138 mm
- Angle version dimensions TITAN S2: 410 mm x 235 mm x 175 mm
- Flush-mounting dimensions TITAN S4: 420 mm x 265 mm x 145 mm
- Class I – IP65 – IK10++ / 120J – VK55 wall version, VK56 ceiling, angle and flush-mounted versions – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- Wall (TITAN S3) or corner (TITAN S2) mounting versions: body and frame in ZP steel – graphite grey colour
- Flush-mounting version (TITAN S4): body and frame in painted 304L stainless steel – polyester powder-coated finish – graphite grey colour or all stainless steel in brushed 316L stainless steel
- Opal polycarbonate diffuser
- Stainless steel vandal-resistant screws
- 2 side cable entries for M20 cable gland – supply terminal block: automatic, dual-entry – sliding, plug-in gear tray
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Option available, on request: with Pro detection. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / 72,000 hr – 5-year warranty
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

*Technical and dimensional data are given for information only and may be modified at any time without notice.  
Please enquire before ordering.*