



## ASL / ESL LED

Surface or flush-mounting luminaires type ASL / ESL LED from SÉCURLITE or technically equivalent:

- Wall version dimensions ASL: 315 x 315 x 85 mm
- Flush-mounting version dimensions ESL: 330 x 330 x 95 mm
- Class I – IP65 - IK10++ / 80J – VK45 surface mounting and VK46 ceiling and flush-mounted versions – 850°C – CRI 80 - SDCM 5 – photobiological hazard: RG0
- ASL surface-mounting version: body and frame in ZP steel, graphite grey colour
- ESL flush-mounting version: body and frame in painted 304L stainless steel – polyester powder-coated finish, graphite grey colour or all stainless steel in brushed 316L stainless steel
- Opal polycarbonate diffuser
- Stainless steel vandal-resistant screws
- 1 rear cable entry – supply terminal block: automatic, dual-entry
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: DALI dimmable. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / 72,000 hr – 5-year warranty
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

*Technical and dimensional data are given for information only and may be modified at any time without notice.  
Please enquire before ordering.*

29/08/2022