



Surface or flush-mounting luminaire type VAUBAN LED from SÉCURLITE or technically equivalent:

- Wall version dimensions VAUBAN A: 390 x 200 x 70 mm
- Flush-mounting version dimensions VAUBAN E: 400 x 210 x 75 mm
- Class I – IP65 – IK11+ / 80J – VK45 surface mounting version and VK46 ceiling and flush-mounted versions – 850°C - CRI 80 - SDCM 3 – photobiological hazard: RG0
- Surface-mounting version VAUBAN A: body and frame in ZP steel – graphite grey colour
- Flush-mounting version VAUBAN E: body and frame in painted 304L stainless steel – polyester powder-coated finish – graphite grey colour or all stainless steel in brushed 316L stainless steel
- Opal polycarbonate diffuser
- Stainless steel vandal-resistant screws
- 1 rear cable entry – supply terminal block: automatic, dual-entry
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hours
- Lumen maintenance: L90B50 / 52,000 hours
- 5-year warranty
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

*Technical and dimensional data are given for information only and may be modified at any time without notice.
Please enquire before ordering.*