



Linear luminaire type URBALINE LED from SÉCURLITE or technically equivalent:

- Wall mounting version: length 370 or 650 or 930 or 1210 mm x 200 mm x 85 mm
- Angle version: length 370 or 650 or 930 or 1210 mm x 157 mm
- Class I – IP65 – 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- End caps in aluminium version IK10++ / 150J – VK56 (angle and ceiling mounted) – VK55 (surface mounted)
- End caps in polycarbonate version IK10+ / 50 J – VK36 (angle and ceiling mounted) – VK35 surface mounted)
- Body: 4 mm thick marine-grade aluminium – opal polycarbonate diffuser
- Reinforced end caps in polycarbonate (50J) or aluminium (150J)
- Colour: anodized aluminium
- Stainless vandal-resistant screws
- Supply terminal block: automatic dual-entry
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with Pro detection, with Pro detection + extinction warning, with Pro detection + standby warning, with Pro detection + radio control, slave version + extinction warning, slave version + standby warning, DALI dimmable + switch dimming + standby warning. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr – lumen maintenance: L90B50 / 52,000 hr - 5-year warranty
- Eligible for the BAR-EQ-110 for detection versions, for the BAT-EQ-127 for Dali version with light output
- ≥ 3000 lm, for the RES-EC-104 for wall mounting version (ceiling mounting only) energy economy certificates
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.