



Modular, upgradeable lighting system. Wide range with multiple versions: wall, hanging, and ceiling fitting, flush-mounting, angle, continuous linear, trunking type SYSTEO LED from SÉCURLITE or technically equivalent:

- Dimensions wall, hanging, and ceiling version SYSTEO UNIT: lengths 891 or 1171 mm
- Dimensions wall, hanging, and ceiling version SYSTEO S lengths 1066 or 1346 mm
- Dimensions wall, hanging, version SYSTEO SLIM lengths 1017 or 1297 mm
- Dimensions flush-mounting version SYSTEO E lengths 1036 or 1316 mm
- Dimensions angle version SYSTEO A45 lengths 1066 or 1346 mm
- Class II – IP65
- SYSTEO UNIT: IK10 / 20 J – VK22 hanging, VK25 wall or ceiling fitting
- SYSTEO S: IK11⁺ / 80J – VK22 hanging, VK45 wall or ceiling fitting
- SYSTEO SLIM: IK11⁺ / 80J – VK22 hanging, VK45 wall or ceiling fitting
- SYSTEO E: IK11⁺ / 80J – VK45 wall or ceiling fitting
- SYSTEO A45: IK11⁺ / 80J – VK45 wall or ceiling fitting
- 850°C – CRI 80 – SDCM 3 – photobiological hazard: RG0
- SYSTEO UNIT: bi-injected polycarbonate body, white colour - opalescent diffuser
- SYSTEO S, SLIM, E, A45: aluminium alloy body, metal alloy end caps and covers, standard colour grey RAL7016 – opalescent diffuser
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with Pro detection, with Pro detection + radio control, DALI dimmable + switch dimming, with Pro detection + radio control + extinction warning, with Pro detection + radio control + standby warning. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- Lumen maintenance: L80B10 / over 72,000 hr – L90B50 / 50,000 hr - 5-year warranty
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.

*Technical and dimensional data are given for information only and may be modified at any time without notice.
Please enquire before ordering.*