



VOILA DURABLE range

Wall or ceiling mounted luminaire type VOILA DURABLE from SÉCURLITE or technically equivalent:

- Dimensions: Ø 340 x 105 mm
- Class II – IP65 – IK10 / 20J – VK26 - 850°C – CRI 80 - SDCM 3 – photobiological hazard: RG0
- Recycled polycarbonate base in white, black, grey
- Opalescent polycarbonate diffuser with 3 captive vandal-resistant stainless steel screws
- Anti-rip-out-skirt, 4 internal fixing points
- Side cable entries for plastic conduit for renovation – supply terminal block: automatic dual-entry for 1.5 mm² conductors
- *CCT, power, luminaire output and efficacy: refer to the technical data sheet according to product code*
- Options available on request: with detection, with Pro detection + extinction or standby warning, with Pro detection + radio control, with Pro detection + extinction or standby + radio control, DALI dimmable + switch dimming. *Refer to the technical data sheet according to product code*
- Range available in 3000 and 4000 K
- You can set 2 different light outputs by using a switch on the driver
- Lumen maintenance: L80B10 / 100,000 hr – 8-year warranty
- Number of detector switching cycles: 1,000 000 at maximum load
- EPD available for ON/OFF version: <https://register.pep-ecopassport.org>
- EPD available for controllable version: <https://register.pep-ecopassport.org>
- Labelled range Origine France Garantie
- Repairable luminaire. Spare parts available on demand.