



Features

- Input voltage: 220–240 V AC, 50/60 Hz
- Input voltage range: 198–264 V AC
- Electrical protection class 1
- IP: 44 (Surface-mounting version)
- IP: 20 (Flush-mounting version)
- IK: 11 / 50 joules
- Incandescent wire test 850 °C / 30 s
- Rated ambient operating temperature: 25 °C
- Operating temperature range : -20 °C ... +35 °C
- Anti-rip-out skirt, 4 internal fixing points
- VK36 flush mounted, VK36 surface mounted
- CRI: 80
- SDCM (Standard Deviation Colour Matching): 5
- Photobiological hazard: RG0
- Energy class C light source
- Lumen maintenance: L90B50 / over 60,000 hours
- Repairable luminaire. Spare parts available on demand
- 5-year guarantee, details of conditions available on securlite.com

Applications

- Bedhead fitting for prison cells, surface-mounting version or flush-mounting version
- Installation positions: refer to installation instructions

Materials

- 1 mm thick ZP steel base
- 1.5 mm thick ZP steel front face
- Opal polycarbonate diffuser
- Stainless vandal-resistant switch
- Closure via 4 tamper-proof stainless screws
- RoHS: the products contain no prohibited substances as defined in the European Directive 2011/65/UE and amendments

Colours / Finish

- Base and front face: polyester powder-coated finish white RAL9003

Technical and dimensional data are given for information only and may be modified at any time without notice. Please enquire before ordering.

06/02/2024

Technical data sheet

P600 - FT0017

Wiring

- 1 × 20.5 mm Ø cable entry
- Supply terminal block: for 1.5 mm² conductors

Fixings

- Body closed using 4 × M6 or M4 stainless fixing screws with 2-point tamper-proof heads

Tools

- M6 bit for 2-point tamper-proof screws for P600 A – code: **98000004**
- M4 bit for 2-point tamper-proof screws for P600 E – code: **98000002**
- Bit-holder screwdriver – code: **98000005**


Approvals

Certificates available:


- CE certificate (as per EN60598-1 / 2-1 / 2-2)
- Incandescent Wire Test certificate (depending on product)

Dimensions


P600 E size 1



P600 E size 2



P600 A



Technical data and order codes

Designation	Colour temperature	Power	Luminaire output	System luminous efficiency	Code
P600 E flush-mount bedhead Size 1 + switch	3000 K	3,3 W	90 lm	27,3 lm/W	53820300
P600 E flush-mount bedhead Size 1 + switch	4000 K	3,3 W	100 lm	30,3 lm/W	53820400
P600 E flush-mount bedhead Size 2 + switch	3000 K	3,3 W	90 lm	27,3 lm/W	53810300
P600 E flush-mount bedhead Size 2 + switch	4000 K	3,3 W	100 lm	30,3 lm/W	53810400
P600 A surface-mount bedhead (switch on right)	3000 K	4,4 W	115 lm	26,1 lm/W	53700300
P600 A surface-mount bedhead (switch on right)	4000 K	4,4 W	130 lm	29,5 lm/W	53700400
P600 A surface-mount bedhead (switch on left)	3000 K	4,4 W	115 lm	26,1 lm/W	53710300
P600 A surface-mount bedhead (switch on left)	4000 K	4,4 W	130 lm	29,5 lm/W	53710400
P600 A surface-mount bedhead w/o switch	3000 K	4,4 W	115 lm	26,1 lm/W	53720300
P600 A surface-mount bedhead w/o switch	4000 K	4,4 W	130 lm	29,5 lm/W	53720400

Operating instruction : www.securlite.com (NOT0635)

Technical and dimensional data are given for information only and may be modified at any time without notice. Please enquire before ordering.

06/02/2024