



JONO PRISON

Features

- Input voltage: 220–240 V AC, 50/60 Hz
- Input voltage range: 198–264 V AC
- Electrical protection class I
- IP: 44 (with socket cover) / IP21 (without socket cover)
- IK: 10 / 20 joules
- Incandescent wire test 850° / 30 s
- Rated ambient operating temperature : 25° C
- Operating temperature range : -20 °C ... +35 °C
- VK22 surface mounted
- CRI: 80
- SDCM (Standard Deviation Colour Matching): 4
- Photobiological hazard: RG0
- Maintenance lumen: L70B50 / 50,000 hours
- 3-year guarantee, details of conditions available on securlite.com

Applications

- Bathroom wall lamp, subject to moderate vandalism
- Installation positions: refer to installation instruction

Materials

- Extruded aluminium base with tamperproof screws, reinforced structure without plug cover
- Opalescent polycarbonate diffuser

Colours / Finish

- Standard colour: white polyester RAL9003

Wiring

- 2 × 10 mm Ø rear cable entry

Visserie

- retained by M4 stainless 2-point tamper-proof screws

Outils *(to be ordered separately)*

- M4 bit for 2-point tamper-proof screws – code: **9800002** *(for the diffuser)*
- M3 bit for 2-point tamper-proof screws – code: **9800001** *(for the plug)*

Technical and dimensional data are given for information only and may be modified at any time without notice. Please enquire before ordering.

05/01/2024

Technical data sheet

Jono Prison- FT0042

Approvals

Certificates available:

- CE certificate (as per EN60598-1 / 2-1)
- Incandescent Wire Test certificate (depending on product)

Dimensions



Technical data and order code

JONO PRISON							
Designation	CCT (K)	Lamp power (W)	Standby power (W)	Source output (lm)	Source luminous efficiency (lm/W)	Length (mm)	Code
JONO PRISON with switch + socket	4000	7	-	750	107	455	31080400
JONO PRISON without switch + socket	4000	7	-	750	107	334	31090400

Operating instruction : www.securlite.com (NOT0645)

Technical and dimensional data are given for information only and may be modified at any time without notice. Please enquire before ordering.

05/01/2024