




## SYSTEO UNIT CLEAR + BATWING OPTICS

### Features

- Input voltage : 220-240V AC, 50/60 Hz
- Input voltage range : 198-264 V AC
- Electrical protection class : 2
- IP : 65
- IK : 10 / 20 joules
- Incandescent wire test 850° / 30 s
- Rated ambient operating temperature : 25° C
- Operating temperature range : -20 °C ... +35 °C
- VK 25 (wall and ceiling-mounted) / 22 (suspended)
- IRC : 80
- SDCM : 3
- Photobiological hazard : RG0
- Energy class C light source
- Lumen maintenance : L80B10 / over 72 000 h
- Lumen maintenance : L90B50 / 50 000 h
- Number of detector switching cycles: 1,000,000 at maximum load.
- Repairable luminaire. Spare parts available on demand
- 5-year guarantee, details of conditions available on [securlite.com](http://securlite.com)



### Applications

- Architectural luminaire with batwing optics for indoor and outdoor environments subject to moderate vandalism
- Street lighting luminaire for optical installation towards the ground
- Conditions of use :
  - UGR and GR to be confirmed for each lighting project.
  - Version with detection : not recommended for outdoor use
  - Installation positions : refer to installation instructions

### Material

- Bi-injected polycarbonate body
- Clear polycarbonate diffuser + batwing flow control optics
- Polycarbonate end caps
- Plug-in terminal block
- Gasket made of SEBS
- RoHS : the products contain no prohibited substances as defined in the European Directive 2011/65/UE and amendments

### Colours / Finish

- Standard colour : white RAL9003

## Wiring

- Supply terminal block : connector conductors
  - 1,5mm<sup>2</sup> (3G1.5mm<sup>2</sup> or 5G1.5mm<sup>2</sup> cable)
  - 2.5mm<sup>2</sup> (3G2.5mm<sup>2</sup> cable only)
- 1 input at one end via cable gland IP67 ISO M20 for cable Ø 6 to 12 mm max
- Not apparent quick power connection

## Screws

- Luminaire is locked by a stainless steel safety screw Torx + Pin (M4 – Tx20)

## Facilities available

- Through wiring - (ex : 54xxxxxx**9101**)
- UV reinforced varnish or anti-graffiti – (ex : 54xxxxxx**9601**)

## Tools *(to be ordered separately)*

- Head insert Torx + Pin (screw M4 – TX20) - code : **98000036**
- Screwdriver insert holder – code : **98000005**
- Remote control for radio controlled version – code : **98000010**

## Accessories *(to be ordered separately)*


- Surface mounting kit : **98540001**
- Suspended mounting kit : **98540002**

## Approvals

Certificates available :

- CE certificate (as per EN60598-1 / 2-1 / 2-3)
- Incandescent wire test certificate (depending on product)

## Dimensions



A (mm)	B wall and ceiling-mounted version (mm)	B suspended version (mm)	KG
891	816	812	2,40 Kg
1171	1096	1092	2,90 Kg

# Technical data sheet

## SYSTEO UNIT CLEAR + BATWING OPTICS – FT0315

### Technical data and order codes

SYSTEO UNIT CLEAR + BATWING OPTICS							
Length L (mm)	CCT (K)	Power (W)	Power in standby (W)	Power factor	Luminaire output (lm)	Luminaire efficacy (lm/W)	Reference
891	3000	9,1	-	0,75	1000	111	<b>54290300</b>
891	4000	9,1	-	0,75	1050	117	<b>54290400</b>
891	3000	14	-	0,85	1600	114	<b>54260300</b>
891	4000	14	-	0,85	1700	121	<b>54260400</b>
1171	3000	19	-	0,90	2250	124	<b>54270300</b>
1171	4000	19	-	0,90	2350	129	<b>54270400</b>

SYSTEO UNIT CLEAR + BATWING OPTICS – slave version + extinction warning							
Length L (mm)	CCT (K)	Power (W)	Power in standby (W)	Power factor	Luminaire output (lm)	Luminaire efficacy (lm/W)	Reference
891	3000	9,0	<0,20	0,75	1000	111	<b>54290304</b>
891	4000	9,0	<0,20	0,75	1050	117	<b>54290404</b>
891	3000	14	<0,20	0,85	1650	118	<b>54260304</b>
891	4000	14	<0,20	0,85	1750	125	<b>54260404</b>
1171	3000	19	<0,20	0,90	2350	124	<b>54270304</b>
1171	4000	19	<0,20	0,90	2450	129	<b>54270404</b>

SYSTEO UNIT CLEAR + BATWING OPTICS – slave version + standby warning							
Length L (mm)	CCT (K)	Power (W)	Power in eco mode <sup>(1)</sup> (W)	Power factor	Luminaire output (lm)	Luminaire efficacy (lm/W)	Reference
891	3000	9,0	2,4	0,75	1000	111	<b>54290305</b>
891	4000	9,0	2,4	0,75	1050	117	<b>54290405</b>
891	3000	14	3,0	0,85	1650	118	<b>54260305</b>
891	4000	14	3,0	0,85	1750	125	<b>54260405</b>
1171	3000	19	3,2	0,90	2350	124	<b>54270305</b>
1171	4000	19	3,2	0,90	2450	129	<b>54270405</b>

SYSTEO UNIT CLEAR + BATWING OPTICS – with Pro detection + radio-control <i>technical specifications and conditions of use for detection : <a href="http://www.securlite.com">www.securlite.com</a> (NOT0420)</i>							
Length L (mm)	CCT (K)	Power (W)	Power in standby (W)	Power factor	Luminaire output (lm)	Luminaire efficacy (lm/W)	Reference
891	3000	10	<0,50	0,77	1000	100	<b>54290316</b>
891	4000	10	<0,50	0,77	1050	105	<b>54290416</b>
891	3000	15	<0,50	0,85	1600	114	<b>54260316</b>
891	4000	15	<0,50	0,85	1700	121	<b>54260416</b>
1171	3000	20	<0,50	0,90	2250	118	<b>54270316</b>
1171	4000	20	<0,50	0,90	2350	123	<b>54270416</b>

SYSTEO UNIT CLEAR + BATWING OPTICS – DALI dimmable + switch dimming							
Length L (mm)	CCT (K)	Power (W)	Power in standby (W)	Power factor	Luminaire output (lm)	Luminaire efficacy (lm/W)	Reference
891	3000	9,0	<0,20	0,75	1000	89	<b>54290321</b>
891	4000	9,0	<0,20	0,75	1050	97	<b>54290421</b>
891	3000	14	<0,20	0,85	1600	114	<b>54260321</b>
891	4000	14	<0,20	0,85	1700	121	<b>54260421</b>
1171	3000	19	<0,20	0,90	2250	124	<b>54270321</b>
1171	4000	19	<0,20	0,90	2350	129	<b>54270421</b>

SYSTEO UNIT CLEAR + BATWING OPTICS – with Pro detection + radio-control + extinction warning <i>technical specifications and conditions of use for detection : <a href="http://www.securlite.com">www.securlite.com</a> (NOT0420)</i>							
Length L (mm)	CCT (K)	Power (W)	Power in standby (W)	Power factor	Luminaire output (lm)	Luminaire efficacy (lm/W)	Reference
891	3000	10	<0,50	0,77	1000	100	<b>54290344</b>
891	4000	10	<0,50	0,77	1050	117	<b>54290444</b>
891	3000	15	<0,50	0,85	1600	114	<b>54260344</b>
891	4000	15	<0,50	0,85	1700	121	<b>54260444</b>
1171	3000	20	<0,50	0,90	2250	118	<b>54270344</b>
1171	4000	20	<0,50	0,90	2350	123	<b>54270444</b>

# Technical data sheet

## SYSTEO UNIT CLEAR + BATWING OPTICS – FT0315

### Technical data and order codes

SYSTEO UNIT CLEAR + BATWING OPTICS – with Pro detection + radio-control + standby warning technical specifications and conditions of use for detection : <a href="http://www.securlite.com">www.securlite.com</a> (NOT0420)							
Length L (mm)	CCT (K)	Power (W)	Power in eco mode <sup>(1)</sup> (W)	Power factor	Luminaire output (lm)	Luminaire efficacy (lm/W)	Reference
891	3000	10	3,2	0,77	1000	100	<b>54290345</b>
891	4000	10	3,2	0,77	1050	117	<b>54290445</b>
891	3000	15	3,6	0,85	1600	114	<b>54260345</b>
891	4000	15	3,6	0,85	1700	121	<b>54260445</b>
1171	3000	20	4,0	0,90	2250	118	<b>54270345</b>
1171	4000	20	4,0	0,90	2350	123	<b>54270445</b>

(1) : eco mode: operating mode with luminous flux reduced to 10% of nominal.

Operating instruction : [www.securlite.com](http://www.securlite.com) (NOT0870)