

# BORGO PRISON

Wall-mounting fitting  
with switch  
for correctional environments.



BVCert. 6037554





Borgo Prison



Mini-Borgo Prison




## FEATURES:

- Very compact cell wall fitting
- Rip-out resistant
- > 65° inclined top
- Vandal-resistant switch
- Body in ZP 10/10 steel
- Frame in ZP 20/10 steel
- Polyester powder-coated finish
- Opalescent polycarbonate diffuser
- CCT 4000 K, CRI min. 80
- Stainless steel vandal-resistant screws
- RAL 9003


## OPTIONS AVAILABLE ON REQUEST:

- 3000 K LEDs
- Switch on the left side


Borgo  
code : 5324 1400




Borgo Prison



Mini-Borgo Prison  
code : 5340 0400



Mini-Borgo Prison



**BORG0 IP 65 with switch**

220-240 V AC / 50 / 60 Hz



direct 532

Length (mm)	Power (W)	Luminaire light output (lm)	Luminaire efficacy (lm / W)	Code switch on right
390	8	725	91	5324 1400
	17	1700	100	5325 1400

**Lumen maintenance:** L80B10 / over 72,000 h  
L90B50 / 52,000 h

**Coding colour temperature 3000 K :** example 4000K : 5324 1400  
replace 4 with 3 3000K : 5324 1300

Vandal-resistant tool (bit) to be ordered separately  
code : 9800 0004

**BORG0 IP 20 with switch and socket**

220-240 V AC / 50 / 60 Hz



direct 532

Length (mm)	Power (W)	Luminaire light output (lm)	Luminaire efficacy (lm / W)	Code switch on the right side
390	8	725	91	5326 1400
	17	1700	100	5327 1400

**Lumen maintenance:** L80B10 / over 72,000 h  
L90B50 / 52,000 h

**Coding colour temperature 3000 K :** example 4000K : 5326 1400  
replace 4 with 3 3000K : 5326 1300

Vandal-resistant tool (bit) to be ordered separately  
code : 9800 0004

**Additional options BORG0**

**Coding:**  
add the corresponding suffix to the product code

example : 5324 1400 ----  
9413 FLAT DUROFLAM® DIFFUSER  
9415 FLAT OPALESCENT PC DIFFUSER


**DETAILS**

Power (W)	Luminaire light output (lm)	Luminaire efficacy (lm/W)	Code switch on the right side
11	925	84	5340 0400

**Lumen maintenance:** L80B10 / over 72,000 h  
L90B50 / 52,000 h

**Coding colour temperature 3000 K :**  
replace 4 with 3

**example** 4000K : 5340 0400  
3000K : 5340 0300

 Vandal-resistant tool (bit) to be ordered separately  
code : 9800 0004

 **DETAILS**

